

JKL PART NUMBER	LENGTH A +/- 2mm	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF6262-30A	262mm	DAYLIGHT WHITE	850	350	5 ± 1	3,000	20,000

*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OFTHE INITIAL RATING.

REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE
	RELEASED	11/27/00

METRIC
THIRD ANGLE PROJECTION

DIMENSIONS ARE IN MILLIMETERS
TOLERANCE UNLESS OTHERWISE SPECIFIED
1 PL +/- 0.2
2 PL +/- 0
ANGLE +/- 0

DRAWN BY: L. WENGSTROM
APPV'D BY / DATE: JK 11/27/00

- CAD DRAWING -
MANUAL REVISIONS NOT PERMITTED

JKL COMPONENTS CORPORATION

TITLE: DUAL LEAD TIP TYPE DAYLIGHT WHITE MINIATURE FLUORESCENT LAMP

SIZE: A
FSCM NO.: 55335
DRAWING NO.: BF 6-30A
SCALE: NONE
RELEASED DATE: 11/27/00
REVISION DATE:
REV. NO.:
SHEET: 1 OF 1