

Ultra Field Stop IGBT, 1200 V, 75 A

FGY75T120SQDN





TO−247−3LD
CASE 340CD

General Description

This Insulated Gate Bipolar Transistor (IGBT) features a robust and cost effective Ultra Field Stop Trench construction, and provides superior performance in demanding switching applications, offering both low on-state voltage and minimal switching loss. The IGBT is well suited for UPS and solar applications. Incorporated into the device is a soft and fast co-packaged free wheeling diode with a low forward voltage.


Features

- Extremely Efficient Trench with Field Stop Technology
- Maximum Junction Temperature: T_J = 175°C
- Low Saturation Voltage: $V_{CE(sat)}$ = 1.7 V (Typ.) @ I_C = 75 A
- 100% of the Parts Tested for I_{LM}(1)
- Soft Fast Reverse Recovery Diode
- Optimized for High Speed Switching
- RoHS Compliant

Applications

- Solar Inverter, UPS

MARKING DIAGRAM



&Y	= **onsemi** Logo
&Z	= Assembly Plant Code
&3	= Date Code (Year & Week)
&K	= Lot Run Traceability Code
FGY75T120SQDN	= Specific Device Code

ORDERING INFORMATION

See detailed ordering and shipping information on page 3 of this data sheet.

ABSOLUTE MAXIMUM RATINGS

(T_J = 25°C unless otherwise stated)

Symbol	Parameter	Value	Unit
V_{CES}	Collector to Emitter Voltage	1200	V
V_{GES}	Gate to Emitter Voltage	±20	V
	Transient Gate to Emitter Voltage	±30	V
I_C	Collector Current @ T_C = 25°C	150	A
	Collector Current @ T_C = 100°C	75	A
I_{LM}(1)	Pulsed Collector Current @ T_C = 25°C	300	A
I_{CM}(2)	Pulsed Collector Current	300	A
I_F	Diode Forward Current @ T_C = 25°C	150	A
	Diode Forward Current @ T_C = 100°C	75	A
I_{FM}	Pulsed Diode Max. Forward Current	300	A
P_D	Maximum Power Dissipation @ T_C = 25°C @ T_C = 100°C	 790 395	W
T_J	Operating Junction Temperature	−55 to +175	°C
T_{stg}	Storage Temperature Range	−55 to +175	°C
T_L	Maximum Lead Temp. for soldering Purposes, 1/8″ from case for 5 s	300	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. V_{CC} = 800 V, V_{GE} = 15 V, I_C = 300 A, R_G = 68 Ω, Inductive Load.
2. Repetitive rating: Pulse width limited by max. junction temperature.

© Semiconductor Components Industries, LLC, 2018

THERMAL CHARACTERISTICS

Symbol	Parameter	Value	Unit
$R_{\theta JC}$ (IGBT)	Thermal Resistance, Junction to Case, Max.	0.19	°C/W
$R_{\theta JC}$ (Diode)	Thermal Resistance, Junction to Case, Max.	0.38	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient, Max.	40	°C/W

ELECTRICAL CHARACTERISTICS OF THE IGBT (T_C = 25°C unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
BV_{CES}	Collector to Emitter Breakdown Voltage	V_{GE} = 0 V, I_C = 500 μA	1200	–	–	V
I_{CES}	Collector Cut-Off Current	V_{CE} = V_{CES}, V_{GE} = 0 V	–	–	400	μA
I_{GES}	G–E Leakage Current	V_{GE} = V_{GES}, V_{CE} = 0 V	–	–	±200	nA
ON CHARACTERISTICS						
$V_{GE(th)}$	G–E Threshold Voltage	I_C = 400 μA, V_{CE} = V_{GE}	4.5	5.5	6.5	V
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	I_C = 75 A, V_{GE} = 15 V	–	1.7	1.95	V
		I_C = 75 A, V_{GE} = 15 V, T_C = 175°C	–	2.3	–	V
DYNAMIC CHARACTERISTICS						
C_{ies}	Input Capacitance	V_{CE} = 20 V, V_{GE} = 0 V, f = 1 MHz	–	9060	–	pF
C_{oes}	Output Capacitance		–	242	–	pF
C_{res}	Reverse Transfer Capacitance		–	137	–	pF
SWITCHING CHARACTERISTICS						
$t_{d(on)}$	Turn-On Delay Time	V_{CC} = 600 V, I_C = 75 A, R_G = 10 Ω, V_{GE} = 15 V, Inductive Load, T_C = 25°C	–	64	–	ns
t_r	Rise Time		–	96	–	ns
$t_{d(off)}$	Turn-Off Delay Time		–	332	–	ns
t_f	Fall Time		–	28	–	ns
E_{on}	Turn-On Switching Loss		–	6.25	–	mJ
E_{off}	Turn-Off Switching Loss		–	1.96	–	mJ
E_{ts}	Total Switching Loss		–	8.21	–	mJ
$t_{d(on)}$	Turn-On Delay Time	V_{CC} = 600 V, I_C = 75 A, R_G = 10 Ω, V_{GE} = 15 V, Inductive Load, T_C = 175°C	–	56	–	ns
t_r	Rise Time		–	80	–	ns
$t_{d(off)}$	Turn-Off Delay Time		–	364	–	ns
t_f	Fall Time		–	88	–	ns
E_{on}	Turn-On Switching Loss		–	8.67	–	mJ
E_{off}	Turn-Off Switching Loss		–	3.2	–	mJ
E_{ts}	Total Switching Loss		–	11.87	–	mJ
Q_g	Total Gate Charge	V_{CE} = 600 V, I_C = 75 A, V_{GE} = 15 V	–	399	–	nC
Q_{ge}	Gate to Emitter Charge		–	74	–	nC
Q_{gc}	Gate to Collector Charge		–	192	–	nC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

ELECTRICAL CHARACTERISTICS OF THE DIODE (T_C = 25°C unless otherwise noted)

Symbol	Parameter	Test Conditions		Min	Typ	Max	Unit
V_{FM}	Diode Forward Voltage	I_F = 75 A	T_C = 25°C	–	3.4	4	V
			T_C = 175°C	–	2.7	–	
t_{rr}	Diode Reverse Recovery Time	V_R = 600 V, I_F = 75 A, dI_F/dt = 500 A/μs	T_C = 25°C	–	99	–	ns
			T_C = 175°C	–	329	–	
Q_{rr}	Diode Reverse Recovery Charge		T_C = 25°C	–	1001	–	nC
			T_C = 175°C	–	5696	–	
I_{rrm}	Diode Reverse Recovery Current		T_C = 25°C	–	20	–	A
			T_C = 175°C	–	34	–	

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

PACKAGE MARKING AND ORDERING INFORMATION

Part Number	Top Mark	Package	Shipping
FGY75T120SQDN	FGY75T120SQDN	TO−247−3LD (Pb−Free)	30 / Tube

TYPICAL CHARACTERISTICS




Figure 1. Typical Output Characteristics (25°C)




Figure 2. Typical Output Characteristics (175°C)




Figure 3. Typical Saturation Voltage Characteristics




Figure 4. Saturation Voltage vs. Case Temperature at Variant Current Level




Figure 5. Saturation Voltage vs. V_{GE} (25°C)




Figure 6. Saturation Voltage vs. V_{GE} (175°C)

TYPICAL CHARACTERISTICS




Figure 7. Capacitance Characteristics




Figure 8. Gate Charge Characteristics




Figure 9. Turn−On Characteristics vs. Gate Resistance




Figure 10. Turn−Off Characteristics vs. Gate Resistance




Figure 11. Turn−On Characteristics vs. Collector Current




Figure 12. Turn−Off Characteristics vs. Collector Current

TYPICAL CHARACTERISTICS




Figure 13. Switching Loss vs. Gate Resistance




Figure 14. Switching Loss vs. Collector Current




Figure 15. Load Current vs. Frequency




Figure 16. SOA Characteristics




Figure 17. Forward Characteristics




Figure 18. Reverse Recovery Time vs. di_F/dt

TYPICAL CHARACTERISTICS




Figure 19. Reverse Recovery Charge vs. di_F/dt




Figure 20. Reverse Recovery Current vs. di_F/dt




Figure 21. Transient Thermal Impedance of IGBT





Figure 22. Transient Thermal Impedance of Diode

MECHANICAL CASE OUTLINE
PACKAGE DIMENSIONS

ON Semiconductor®




TO−247−3LD
CASE 340CD
ISSUE A

DATE 18 SEP 2018

NOTES:

A. THIS PACKAGE DOES NOT CONFORM TO ANY STANDARDS.
B. ALL DIMENSIONS ARE IN MILLIMETERS.
C. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH AND TIE BAR PROTRUSIONS.
D. DIMENSION AND TOLERANCE AS PER ASME Y14.5-2009.



DIM	MILLIMETERS		
	MIN	NOM	MAX
A	4.58	4.70	4.82
A1	2.20	2.40	2.60
A2	1.80	2.00	2.20
D	20.32	20.57	20.82
E	15.37	15.62	15.87
E2	4.12	4.32	4.52
e	~	5.45	~
L	19.90	20.00	20.10
L1	3.69	3.81	3.93
Q	5.34	5.46	5.58
b	1.10	1.20	1.30
b2	2.10	2.24	2.39
b4	2.87	3.04	3.20
c	0.51	0.61	0.71
D1	16.63	16.83	17.03
D2	0.51	0.93	1.35
E1	13.40	13.60	13.80

GENERIC MARKING DIAGRAM*



XXXX = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
G = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	**98AON13857G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**TO−247−3LD**	**PAGE 1 OF 1**

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

onsemi, ONSEMI , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Email Requests to: orderlit@onsemi.com

onsemi Website: www.onsemi.com

TECHNICAL SUPPORT
North American Technical Support:
Voice Mail: 1 800−282−9855 Toll Free USA/Canada
Phone: 011 421 33 790 2910

Europe, Middle East and Africa Technical Support:
Phone: 00421 33 790 2910
For additional information, please contact your local Sales Representative

◊