

T300RGB-24V-KIT

4.4W RGB LED Tape Light Kit, High Output

SPECIFICATION FOR TAPE:

Input Voltage	24VDC												
Wattage	4.4W/ft												
Output	<table border="1"> <thead> <tr> <th colspan="2">RGB30K</th> </tr> </thead> <tbody> <tr> <td>RGBW</td><td>289 lm/ft</td> </tr> <tr> <td>Red (620-625nm)</td><td>22 lm/ft</td> </tr> <tr> <td>Green (520-525nm)</td><td>62 lm/ft</td> </tr> <tr> <td>Blue (465-470nm)</td><td>14 lm/ft</td> </tr> <tr> <td>3000K</td><td>180 lm/ft</td> </tr> </tbody> </table>	RGB30K		RGBW	289 lm/ft	Red (620-625nm)	22 lm/ft	Green (520-525nm)	62 lm/ft	Blue (465-470nm)	14 lm/ft	3000K	180 lm/ft
RGB30K													
RGBW	289 lm/ft												
Red (620-625nm)	22 lm/ft												
Green (520-525nm)	62 lm/ft												
Blue (465-470nm)	14 lm/ft												
3000K	180 lm/ft												
IP Rating	IP20												
CRI	90+												
Dimmable	0-10V, ELV, MLV												
Max. Run Length	16 ft												
Field Cuttable	4" cut points												
Beam Angle	120°												
LED Tape Operating Temp.	-13 °F to 140 °F												
LED Tape Warranty	3 year limited*												
LED Tape Adhesive	3M™ VHB mounting adhesive on back												
LED Tape Dimensions	0.47" W x 0.08" H (12.0mm x 2.0mm)												
LED Tape Lifetime	50,000 Hours												
LED Tape Warranty	5 year limited												
Incl. Power Supply	120 VAC to 24VDC, 96W CAPACITY												



Applications:

- Indoor signage
- Indirect lighting
- Accent lighting
- Undercabinet

INCLUDED IN KIT



**T300RGB-XXV-KIT
16FT TAPELIGHT REEL**

1 OF EACH



**PW9624V
24V POWER SUPPLY**

1 OF EACH



RGB/W RECIEVER

1 OF EACH



RGB/W REMOTE

1 OF EACH



**GRIPPER-TT-RGBW
GRIPPER-TW-RGBW**

2 OF EACH

T300RGB-24V-KIT

4.4W RGB LED Tape Light Kit, High Output

INCLUDED IN KIT



RGB-TOUCH-WM-HW WALL MOUNTED TOUCH CONTROLLED

1 OF EACH

WIRING DIAGRAM

