



Technical characteristics

Degree of protection acc. to IEC IP68
60529

Material (cable glands) Metal

Technical characteristics

RoHS
RoHS exemptions

compliant with exemption
6c: Copper alloy containing up to 4 % lead by weight

Identification	Size	Clamping range (mm)	Part number	Drawing (dimensions in mm)			
Cable gland, EMC version	M20	4 ... 6,5	19 62 000 5081	cable-Ø D	SW	E	shield-Ø B
	M20	6,5 ... 9,5	19 62 000 5080	6.5 ... 9.5	22	24.4	3,5 ... 8,5
	M20	7 ... 10,5	19 62 000 5082	4 ... 6.5	22	24.4	2,5 ... 6,5
	M20	9 ... 13	19 62 000 5084	7 ... 10.5	22	24.4	6,5 ... 10,5
	M25	6,5 ... 9,5	19 62 000 5090	9 ... 13	22	24.4	6,5 ... 10,5
	M25	9 ... 13	19 62 000 5092	6.5 ... 9.5	22	31.2	3 ... 8
	M32	11,5 ... 15,5	19 62 000 5094	9 ... 13	28	31.2	4,8 ... 8
	M32	14 ... 18	19 62 000 5096	11.5 ... 15.5	35	38.5	8 ... 13,5
	M40	17 ... 20,5	19 62 000 5097	14 ... 18	35	38.5	9 ... 14,5
	M40	20 ... 25	19 62 000 5098	17 ... 20.5	43	47.3	15 ... 20
				20 ... 25	43	47.3	15 ... 20

