CEL

NPN SILICON HIGH FREQUENCY TRANSISTOR

UPA814T

FEATURES

- **SMALL PACKAGE STYLE:**
  2 NE688 Die in a 2 mm x 1.25 mm package
- **LOW NOISE FIGURE:**
  NF = 1.5 dB TYP at 2 GHz
- **HIGH GAIN BANDWIDTH:** f_T = 9 GHz
- **HIGH COLLECTOR CURRENT:** 100 mA

DESCRIPTION

NEC's UPA814T is two NPN high frequency silicon epitaxial transistors encapsulated in an ultra small 6 pin SMT package. Each transistor is independently mounted and easily configured for either dual transistor or cascode operation. The high f_T, low voltage bias and small size make this device suited for various hand-held wireless applications.


ABSOLUTE MAXIMUM RATINGS[1] (T_A = 25°C)

SYMBOLS	PARAMETERS	UNITS	RATINGS
V_{CBO}	Collector to Base Voltage	V	9
V_{CEO}	Collector to Emitter Voltage	V	6
V_{EBO}	Emitter to Base Voltage	V	2
I_C	Collector Current	mA	100
P_T	Total Power Dissipation 1 Die 2 Die	 mW mW	 110 200
T_J	Junction Temperature	°C	150
T_{STG}	Storage Temperature	°C	-65 to +150

Note: 1.Operation in excess of any one of these parameters may result in permanent damage.

OUTLINE DIMENSIONS (Units in mm)

PACKAGE OUTLINE S06



PIN OUT
1. Collector Transistor 1
2. Base Transistor 2
3. Collector Transistor 2
4. Emitter Transistor 2
5. Emitter Transistor 1
6. Base Transistor 1

Note:
Pin 3 is identified with a circle on the bottom of the package.


ELECTRICAL CHARACTERISTICS (T_A = 25°C)

PART NUMBER PACKAGE OUTLINE			UPA814T S06		
SYMBOLS	PARAMETERS AND CONDITIONS	UNITS	MIN	TYP	MAX
I_{CBO}	Collector Cutoff Current at V_{CB} = 5V, I_E = 0	μA			0.1
I_{EBO}	Emitter Cutoff Current at V_{EB} = 1 V, I_C = 0	μA			0.1
h_{FE}[1]	Forward Current Gain at V_{CE} = 1 V, I_C = 3 mA		80	110	160
f_T	Gain Bandwidth at V_{CE} = 3 V, I_C = 20 mA, f = 2 GHz	GHz		9.0	
Cre[2]	Feedback Capacitance at V_{CB} = 1 V, I_E = 0, f = 1 MHz	pF		0.75	0.85
$\|S_{21E}\|^2$	Insertion Power Gain at V_{CE} = 3 V, I_C =20 mA, f = 2 GHz	dB		6.5	
NF	Noise Figure at V_{CE} = 3 V, I_C = 7 mA, f = 2 GHz	dB		1.5	
h_{FE1}/h_{FE2}	h_{FE} Ratio: h_{FE1} = Smaller Value of Q_1, or Q_2 h_{FE2} = Larger Value of Q_1 or Q_2		0.85		


Notes: 1. Pulsed measurement, pulse width ≤ 350 μs, duty cycle ≤ 2 %.
2. The emitter terminal should be connected to the ground terminal of the 3 terminal capacitance bridge.
For Tape and Reel version use part number UPA814T-T1, 3K per reel.

TYPICAL PERFORMANCE CURVES (T_A = 25°C)


TOTAL POWER DISSIPATION vs. AMBIENT TEMPERATURE




COLLECTOR CURRENT vs. BASE TO EMITTER VOLTAGE




COLLECTOR CURRENT vs. COLLECTOR TO EMITTER VOLTAGE




DC CURRENT GAIN vs. COLLECTOR CURRENT



GAIN BANDWIDTH PRODUCT vs. COLLECTOR CURRENT




INSERTION POWER GAIN vs. COLLECTOR CURRENT




TYPICAL PERFORMANCE CURVES (T_A = 25°C)


NOISE FIGURE vs. COLLECTOR CURRENT




FEEDBACK CAPACITANCE vs. COLLECTOR TO BASE VOLTAGE



MAXIMUM AVAILABLE GAIN/INSERTION POWER GAIN vs. FREQUENCY



NOISE FIGURE vs. FREQUENCY



ORDERING INFORMATION

PART NUMBER	QUANTITY	PACKAGING
UPA814T-T1-A	3000	Tape & Reel

Life Support Applications
These NEC products are not intended for use in life support devices, appliances, or systems where the malfunction of these products can reasonably be expected to result in personal injury. The customers of CEL using or selling these products for use in such applications do so at their own risk and agree to fully indemnify CEL for all damages resulting from such improper use or sale.

EXCLUSIVE NORTH AMERICAN AGENT FOR NEC RF, MICROWAVE & OPTOELECTRONIC SEMICONDUCTORS
CEL CALIFORNIA EASTERN LABORATORIES • Headquarters • 4590 Patrick Henry Drive • Santa Clara, CA 95054-1817 • (408) 988-3500 • Telex 34-6393 • FAX (408) 988-0279
24-Hour Fax-On-Demand: 800-390-3232 (U.S. and Canada only) • Internet: http://WWW.CEL.COM
DATA SUBJECT TO CHANGE WITHOUT NOTICE
PRINTED IN USA ON RECYCLED PAPER -1/99

CEL California Eastern Laboratories

4590 Patrick Henry Drive
Santa Clara, CA 95054-1817
Telephone: (408) 919-2500
Facsimile: (408) 988-0279

Subject: Compliance with EU Directives

CEL certifies, to its knowledge, that semiconductor and laser products detailed below are compliant with the requirements of European Union (EU) Directive 2002/95/EC Restriction on Use of Hazardous Substances in electrical and electronic equipment (RoHS) and the requirements of EU Directive 2003/11/EC Restriction on Penta and Octa BDE.

CEL Pb-free products have the same base part number with a suffix added. The suffix –A indicates that the device is Pb-free. The –AZ suffix is used to designate devices containing Pb which are exempted from the requirement of RoHS directive (*). In all cases the devices have Pb-free terminals. All devices with these suffixes meet the requirements of the RoHS directive.

This status is based on CEL's understanding of the EU Directives and knowledge of the materials that go into its products as of the date of disclosure of this information.

Restricted Substance per RoHS	Concentration Limit per RoHS (values are not yet fixed)	Concentration contained in CEL devices	
Lead (Pb)	< 1000 PPM	-A	-AZ
		Not Detected	(*)
Mercury	< 1000 PPM	Not Detected	
Cadmium	< 100 PPM	Not Detected	
Hexavalent Chromium	< 1000 PPM	Not Detected	
PBB	< 1000 PPM	Not Detected	
PBDE	< 1000 PPM	Not Detected	

If you should have any additional questions regarding our devices and compliance to environmental standards, please do not hesitate to contact your local representative.

Important Information and Disclaimer: Information provided by CEL on its website or in other communications concerting the substance content of its products represents knowledge and belief as of the date that it is provided. CEL bases its knowledge and belief on information provided by third parties and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. CEL has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. CEL and CEL suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.
In no event shall CEL's liability arising out of such information exceed the total purchase price of the CEL part(s) at issue sold by CEL to customer on an annual basis.
See CEL Terms and Conditions for additional clarification of warranties and liability.