THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT PART #	STUD SIZE		DIMENSIONS in. [mm]				
	ENGLISH	METRIC	L ±.03 [0,8]	W ±.01 [0,3]	C ±.015 [0,4]	M ±.03 [0,8]	H ±.01 [0,3]
E10-6FB	#6	M3	.75 [19,1]	.31 [7,9]	.22 [5,6]	.55 [14,0]	.15 [3,8]
E10-8FB	#8	M4	.78 [19,8]	.37 [9,4]	.22 [5,6]	.55 [14,0]	.17 [4,3]
E10-10FB	#10	M5	.78 [19,8]	.37 [9,4]	.23 [5,8]	.55 [14,0]	.20 [5,1]
E10-14FB	1/4"	M6	.89 [22,6]	.50 [12,7]	.30 [7,6]	.60 [15,2]	.27 [6,9]

UL & CSA TOOLS
CT-100A CT-200 CT-600-A (CT-570CH) CT-1570 CT-1701 (P10) CT-2500 (CT-2570CH)

PANDUIT APPROVED TOOLS
CT-160 CT-260

NOTES:

1. UL LISTED & CSA CERTIFIED FOR:
   A. #12-10 AWG [4,0-6,0 mm²] SOLID OR STRANDED COPPER WIRE
   B. 302°F [150°C] MAX. OPERATING TEMPERATURE
   C. 2000 VOLTS MAX
2. MATERIAL:
   A. STAMPING: .04" [1,0] THK COPPER, TIN PLATED
3. WIRE STRIP LENGTH: 9/32" $^{+1/32}_{-0}$ [7,1mm $^{+0,8}_{-0}$]
4. SEE www.panduit.com FOR PACKAGE QUANTITIES
5. DIMENSIONS IN BRACKETS ARE METRIC EQUIVALENT



c UL us
LISTED
587H
E52164

CSA
CERTIFIED
LR31212

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
00	02/18	JHNU	TMR	RGB	RELEASED	00123SH

TITLE
STRONGHOLD FORK TERMINAL
NON-INSULATED, BUTTED SEAM #12-10 AWG
CUSTOMER DRAWING

ITEM REVISION NAME: 00123SHK/00
DATASET FILE NAME: 00123SHK_DC/00

PANDUIT

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]
.X ± .XXX ±
.XX ± ANGLES ±
THIRD ANGLE PROJECTION

MATERIAL: SEE NOTES

DRAWING NUMBER: SH41256

DRAWN BY	DATE	CHK	SCALE	SHEET 1 OF 1	SIZE
JHNU	2/18	TMR	N.T.S.		A

D10100DA/12