




Micro Commercial Components



Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

DB3TG

**SILICON
BIDIRECTIONAL
DIAC**

DO-35G

Features

- The three layer, two terminal, axial lead, hermetically sealed diacs are designed specifically for triggering thyristors.
- Lead Free Finish/Rohs Compliant (Note1) ("P" Suffix designates Compliant. See ordering information)
- Moisture Sensitivity: Level 1 per J-STD-020C
- Intended for use in thyristors phase control , circuits for lamp dimming, universal motor speed control ,and heat control.

Maximum Ratings

- Operating Temperature: -40°C to +125°C
- Storage Temperature: -40°C to +125°C
- Thermal Resistance Junction to Lead: 167°C/W
- Thermal Resistance Junction to Ambient: 400°C/W

Electrical Characteristics @ 25°C Unless Otherwise Specified

Power dissipation on Printed Circuit(l=10mm)	P_C	150mW	$T_A=65^\circ\text{C}$
Repetitive Peak on-state Current	I_{TRM}	2.0A	$t_p=10\mu\text{s}, f=120\text{Hz}$
Breakover Voltage	V_{BO}	Min Typ Max 30 32 34V	$C=22\text{nF}(\text{Note } 3)$
Breakover Voltage Symmetry	$ +V_{BO} $ $- -V_{BO} $	$\pm 2\text{V}$	$C=22\text{nF}(\text{Note } 3)$
Output Voltage(Note 2)	$V_{o(\min)}$	5V	
Dynamic breakover voltage (N o t e 2)	ΔV	9V(Min)	V_{BO} and V_F at 10mA
Breakover Current(Note 2)	$I_{BO(\max)}$	15 μA	$C=22\text{nF}$
Rise Time(Note 2)	T_r	2 $\mu\text{s}(\text{max})$	
Leakage Current(Note 2)	$I_{B(\max)}$	10 μA	$V_B=0.5V_{BO(\max)}$


Note: 1. Lead in Glass Exemption Applied, see EU Directive Annex 7(C)-I.

2. Electrical characteristics applicable in both forward and reverse directions.

3. Connected in parallel with the devices.

DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	---	.150	---	3.8	
B	---	.079	---	2.00	
C	---	.020	---	.52	
D	1.083	---	27.50	---	

Typical Performance Characteristics



V_{BO} : Break-Over Voltage
 I_{BO} : Break-Over Current
 ΔV : Dynamic Breakover Voltage
 I_B : Leakage Current at $V_B = 0.5 \cdot V_{BO}$
 V_F : Voltage at Current $I_F = 10\text{mA}$

Diagram 1 : Test circuit




Figure 1. Admissible Power Dissipation Curve




Figure 2. Relative Variation of VBO versus Junction Temperature





Figure 3. Repetitive Peak Pulse Current versus Pulse Duration (maximum values)





Micro Commercial Components

Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel: 5Kpcs/Reel
Part Number-AP	Ammo Packing: 5Kpcs/Ammo Box
Part Number-BP	Bulk: 100Kpcs/Carton

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com