

Industrial PC - BL BPC 2001 - 2701711

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



IP20-rated fanless industrial box PC (BPC) with energy-efficient Intel® quad-core Celeron® N2930 processor with 2 GB RAM.

Shown without optional BL BPC
2000 SATA Expansion tray.

Product Description

The Basicline BPC 2000 is a configurable box PC that can be mounted either directly on a wall or on a DIN rail. The Basicline BPC 2000 utilizes Intel® quad-core Celeron® N2930 processor, chosen for its balance of processing power and energy efficiency. The small footprint, fanless design, and rich I/O capability make the Basicline BPC 2000 a product that can be used in a wide variety of applications. The three built-in COM ports enable connections to legacy RS-232 devices. One of the COM ports can also be configured for RS-422 or RS-485 protocols.

Drive tray is only included when originally configured with SSD or HDD mass storage options.

Why buy this product

- ✓ Custom configurable
- ✓ Embedded operating system support
- ✓ DIN rail- and wall-mounting options
- ✓ Three COM ports
- ✓ Fanless design
- ✓



Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	1.000 g
Custom tariff number	84714100
Country of origin	Taiwan

Technical data

Note

Industrial PC - BL BPC 2001 - 2701711

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Computer data

Processor	Intel® Celeron® N2930 1.83 GHz/2.16 GHz
Cooling	passive
Operating systems	without operating system
RAM	2 GB DDR3 SODIMM
Mass storage	without mass storage
Network	2x Ethernet (10/100/1000 Mbps), RJ45
Network chipset	Realtek® 8111F PCI-E
Interfaces	1x COM (RS-232/422/485)
	2x COM (RS-232)
	3x USB 2.0
	1x USB 3.0
Monitor output	2x DisplayPort
Slots	without slots
Optical drive	Without drive
Realtime clock	Yes (battery-backed)
Service life of battery	5 years (typical)

General

Mounting type	Wall mounting
Weight	1.6 kg

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 50 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Permissible humidity (operation)	5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	5 % ... 95 % (non-condensing)
Vibration (operation)	DIN EN 60068-2-6
Shock	15g, 11 ms in accordance with IEC 60068-2-27

Device supply

Supply voltage	24 V DC
Supply voltage range	19.2 V DC ... 28.8 V DC
Power consumption	typical
Power supply unit	24 V DC ±20 %

Industrial PC - BL BPC 2001 - 2701711

Technical data

Standards and Regulations

Shock	15g, 11 ms in accordance with IEC 60068-2-27
Vibration (operation)	DIN EN 60068-2-6

Classifications

eCl@ss

eCl@ss 4.0	27250315
eCl@ss 4.1	27250315
eCl@ss 5.0	27259205
eCl@ss 5.1	27242401
eCl@ss 6.0	27259205
eCl@ss 7.0	27242692
eCl@ss 8.0	19200101
eCl@ss 9.0	19200101

ETIM

ETIM 4.0	EC001413
ETIM 5.0	EC001413

Approvals

Approvals

Approvals

UL Listed / cUL Listed / cULus Listed

Ex Approvals

Approval details

UL Listed  http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 238705

cUL Listed  http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 238705
--

Industrial PC - BL BPC 2001 - 2701711

Approvals

cULus Listed 

Accessories

Accessories

Adapter cable

DP TO VGA ADPTR - 2400173

DisplayPort to VGA video adapter



DP TO DVI ADPTR - 2400174

DisplayPort to DVI-i video adapter



Assembly adapter

Assembly adapters - UTA 107/30 - 2320089



Universal DIN rail adapter

Buffer module

Buffer module - PC-PWR-FLTR-1 - 2402832



The PC-PWR-FLTR-1 buffers incoming power until operating voltage is reached. For use with 24 V DC power sources with ascend times over 100 ms. 4 A max.

Industrial PC - BL BPC 2001 - 2701711

Accessories

Mounting material

Removable hard drive tray - BL BPC 2000 2.5" SATA BAY - 2403331

The BL BPC 2000 2.5" SATA BAY is for adding a HDD/SSD mass storage drive to the BL BPC 2000



Storage medium

Memory - IPC 4 GB CFAST KIT - 2400168



4 GB CFast® card

Memory - IPC 8 GB CFAST KIT - 2400169



8 GB CFast® card

Memory - IPC 16 GB CFAST KIT - 2400170



16 GB CFast® card

Industrial PC - BL BPC 2001 - 2701711

Accessories

Memory - IPC 32 GB CFAST KIT - 2402978



32 GB CFast® card