



SM-8 DUAL PNP MEDIUM POWER
TRANSISTORS

ISSUE 1 - NOVEMBER 1995

ZDT758



PARTMARKING DETAIL – T758



SM-8
(8 LEAD SOT223)

ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	V_{CBO}	-400	V
Collector-Emitter Voltage	V_{CEO}	-400	V
Emitter-Base Voltage	V_{EBO}	-5	V
Peak Pulse Current	I_{CM}	-1	A
Continuous Collector Current	I_C	-0.5	A
Operating and Storage Temperature Range	$T_j:T_{stg}$	-55 to +150	°C

THERMAL CHARACTERISTICS

PARAMETER	SYMBOL	VALUE	UNIT
Total Power Dissipation at $T_{amb} = 25^{\circ}C^*$	P_{tot}		
Any single die "on"		2.25	W
Both die "on" equally		2.75	W
Derate above $25^{\circ}C^*$			
Any single die "on"		18	mW/ °C
Both die "on" equally		22	mW/ °C
Thermal Resistance - Junction to Ambient*			
Any single die "on"		55.6	°C/ W
Both die "on" equally		45.5	°C/ W

* The power which can be dissipated assuming the device is mounted in a typical manner on a PCB with copper equal to 2 inches square.

ZDT758


ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}\text{C}$ unless otherwise stated).

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	-400			V	$I_C = -100\mu\text{A}$
Collector-Emitter Breakdown Voltage	$V_{CEO(SUS)}$	-400			V	$I_C = -10\text{mA}^*$
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	-5			V	$I_E = -100\mu\text{A}$
Collector Cutoff Current	I_{CBO}			-100	nA	$V_{CB} = -320\text{V}$
Collector Cutoff Current	I_{CES}			-100	nA	$V_{CE} = -320\text{V}$
Emitter Cutoff Current	I_{EBO}			-100	nA	$V_{EB} = -4\text{V}$
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$			-0.30 -0.25 -0.50	V V V	$I_C = -20\text{mA}$, $I_B = -1\text{mA}$ $I_C = -50\text{mA}$, $I_B = -5\text{mA}^*$ $I_C = -100\text{mA}$, $I_B = -10\text{mA}^*$
Base-Emitter Saturation Voltage	$V_{BE(sat)}$			-0.9	V	$I_C = -100\text{mA}$, $I_B = -10\text{mA}^*$
Base-Emitter Turn On Voltage	$V_{BE(on)}$			-0.9	V	$I_C = -100\text{mA}$, $V_{CE} = -5\text{V}^*$
Static Forward Current Transfer Ratio	h_{FE}	50 50 40				$I_C = -1\text{mA}$, $V_{CE} = -5\text{V}$ $I_C = -100\text{mA}$, $V_{CE} = -5\text{V}^*$ $I_C = -200\text{mA}$, $V_{CE} = -10\text{V}^*$
Transition Frequency	f_T	50			MHz	$I_C = -20\text{mA}$, $V_{CE} = -20\text{V}$ $f = 20\text{MHz}$
Output Capacitance	C_{obo}			20	pF	$V_{CB} = -20\text{V}$, $f = 1\text{MHz}$
Switching times	t_{on} t_{off}		140 2000		ns ns	$I_C = -100\text{mA}$, $V_{CE} = -100\text{V}$ $I_{B1} = 10\text{mA}$, $I_{B2} = -20\text{mA}$


*Measured under pulsed conditions. Pulse width=300 μs . Duty cycle $\leq 2\%$

ZDT758


TYPICAL CHARACTERISTICS




$V_{CE(sat)}$ v I_C




$V_{CE(sat)}$ v I_C



h_{FE} v I_C



$V_{BE(sat)}$ v I_C



$V_{BE(on)}$ v I_C