
ORIENT DISPLAY
Your Total LCD Solution Provider

Specification for LED Backlight



JAZZ-AE-R

Revision A

JAZZ	LED Backlight
AE	Serial AE, Dimension 71.20 X 48.50 X 5.20 mm
R	Red
/	RoHS Compliant
/	Pair with Glass Panel JAZZ-AC
/	Pair with Touch Panel JAZZ-AT

ORIENT DISPLAY (North America) Limited
220 Royal Crest Court, Unit 6, Markham, Ontario, L3R9Y2, Canada
Tel: 905-477-1166 Fax: 905-477-1782 http://www.orientdisplay.com


JAZZ-AE-R

LED BACKLIGHT
FOR LCD DISPLAY


1. 结构尺寸 MECHANICAL OUTLINE

(未注尺寸公差Unspecified Tolerances is ± 0.3)

COLOR : RED
颜 色 : 红色



2. 电路图 CIRCUIT DIAGRAM (LED 1X5=5 SMD dies)



3. 保存和焊接条件 STORAGE & SOLDERING CONDITIONS:

- **Store with care. Storing the units in bad condition will cause the reflector sheet and decrease it's adhesive power. Storage The products under the condition: temperature (25°c ±10°C) and humidity (65%RH±20%RH) our recommendation.**
- **The Soldering Temperature is 260±5°C and Soldering Time should be less than 3 sec, and soldering iron power should be less than 30W.**
- **The soldering point should be farther than 1.6mm (1/10") from body .**

- 注意保存,保存条件不好时,会降低反光膜(扩散膜)导光片(反射壳)的粘附力。
  推荐保存条件: 温度 **25°C±10°C**
  湿度 **65%RH±20%RH**
- 焊接温度 **260°C±5°C,** 焊接时间小于3秒
  烙铁功率小于 **30W.**
- 焊接点应离焊接实体大于1.6mm.
- 产品对静电敏感,保存及焊接时必须有防静电措施.

- The product is sensitive to static electricity,So it's necessary to take proper steps when storing and soldering.

2						DESIGN: RZK 设计
1						CHECKED: 检查
ISSUE	AMENDMENT	DATE				COUNTERSIGN: 会签
DRAWING NO.: JAZZ-AE-R		REV: A0	SHEET: 1 OF 2		DATE: 2009.7.24	APPROVED: 批准

ORIENT DISPLAY (North America) Limited
220 Royal Crest Court, Unit 6, Markham, Ontario, L3R9Y2, Canada
Tel: 905-477-1166 Fax: 905-477-1782 http://www.orientdisplay.com

4.极限参数 ABSOLUTE MAXIMUM RATINGS (SINGLE LED)

(除非特别说明，环境温度Ta=25°C. Unless specified,The Ambient temperature Ta=25°C)

项目 Item	符号 Symbel	条件 Conditions	值 Rating	单位 Unit
* 极限直流正向电流 Absolute maximum forward current	Ifm		25	mA
* 脉冲驱动时极限正向电流 Peak forward current	Ifp	1 msec脉冲,1/10占空比 1 msec Plus 10% Duty Cycle	60	mA
反向电压 Reverse Voltage	Vr		5	V
* 极限功耗 Power dissipation	Pd		50	mW
工作温度 Operating Temperature Range	Topr		-30~+70°C	°C
贮存温度 Storage Temperature Range	Tstg		-40~+80°C	°C

* 当工作温度高于25°C时,Ifm、Ifp和Pd必须降低；电流降低率是 -0.36 mA/°c(直流驱动),或 -0.86 mA/°c(脉冲驱动), 功率降低率是 -0.75 mW/°C. 产品工作电流不能大于对应的工作条件温度 Ifm 或Ifp 的 60 %.

For operation above 25°C,The Ifm Ifp & Pd must be derated,the Curent derating is -0.36 mA/°c for DC drive and -0.86 mA/°c for Pulse drive,the Power dissipation is -0.75 mW/°c. The product working current must not more than the 60 % of the Ifm ir Ifp according to the working temperature.


5.电光特性 ELECTRICAL-OPTICAL CHARACTERISTICS

(除非特别说明，环境温度Ta=25°C. Unless specified,The Ambient temperature Ta=25°C)

项目 Item	符号 Symbol	最小值 min.	典型值 typ.	最大值 max.	单位 Unit	测定条件 Condition
正向电压 Forward Voltage	Vf		3.3		V	If= 50 mA
反向电流 Reverse Current	Ir			10	Am	Vr= 0.8 V
峰值波长 Peak wave length	λρ	620		625	nm	If= 50 mA
频谱半宽度 Spectral Line Half width	△λ		25		nm	If= 50 mA
* 亮度 Luminance	Lv				cd/m²	If= 50 mA

* 亮度值是5个测量点的平均值,亮度最大值比最小值一般小于等于1.3.使用 ST-86LA 亮度计测量,测量光圈 ø 5 mm.

The luminance is the average value of 5 points, and,The Lvmax./Lvmin. is 1.3 max. The measurement instrument is ST-86LA luminance,Colorimeter.The caperture is ø 5 mm.



DESIGN: 设计	RZK
CHECKED: 检查	
COUNTERSIGN: 会签	
APPROVED: 批准	