# Specification Sheet

Part Number: 596-00904




Made with UV-stable inks and materials for durability and weather resistance.
Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.

High abrasion and scuff resistance for high-performance labeling.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Arc Flash Label, DANGER APPROPRIATE PPE REQUIRED, 5.0" x 3.75", PET, Red/White, 10/pkg

| | |
|---|---|
| Article Number | 596-00904 |
| Type | AF5X35D |
| Color | Red (RD) |
| Quantity Per | pack |

| | |
|---|---|
| Product Description | HellermannTyton makes it easier than ever for solar installers to meet PV labeling codes. Solar Label Convenience Packs allow installers to quickly and economically purchase high quality preprinted NEC code-compliant solar installation labels. Packaged in 10-count quantities to meet the needs of smaller scale solar installations and independent contractors, Solar Label Convenience Packs are available in HellermannTyton's most popular preprinted NEC code-compliant solar label formats. Each Solar Label Convenience Pack contains 10 solar installation labels. Choose from a variety of regular and reflective preprinted labels. For enhanced durability, clear laminate overlay labels are also available in a convenience pack. |
| Short Description | Arc Flash Label, DANGER APPROPRIATE PPE REQUIRED, 5.0" x 3.75", PET, Red/White, 10/pkg |
| Global Part Name | AF5X35D-840/281-RD |
| Width W (Imperial) | 5.00 |
| Width W (Metric) | 127 |
| Thickness T (Imperial) | 0.0025 |
| Thickness T (Metric) | 64.0 |
| Height H (Imperial) | 3.75 |
| Height H (Metric) | 95.25 |
| Material | Type 840/281, Polyester, UV-stabilized, clear polyester laminate (840/281) |

| | |
|---|---|
| Material Shortcut | 840/281 |
| Adhesive | Acrylic |
| Halogen Free | Yes |
| UV Resistant (Yes/No) | Yes |
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Certification/Specification | NEC2014 NEC2017 NEC2020 NEC2011 NEC2023 |
| Warranty (US) | Yes |
| UL Recognized (US) | Yes |
| Package Quantity (Imperial) | 10 |
| Package Quantity (Metric) | 10 |
| Customs Number | 3919905060 |
| Labels per Column | 1 |
| Labels per Row | 1 |

© 2023 HellermannTyton. All Rights Reserved.