


PIN RECEPTACLES

FOR .065" - .082" DIAMETER PINS

0395

0395-X-15-XX-07-XX-10-0

Swage mount in .096 hole




Basic Part Number	Board Thickness	Length V
0395-1	.031	.062
0395-2	.062	.094
0395-3	.094	.125
0395-4	.125	.156
0395-5	.188	.219

8016

8016-0-15-XX-07-XX-10-0


Press-fit in .131 mounting hole



0350

0350-0-15-XX-07-XX-10-0


Hex press-fit in .129±.002 plated through-hole



0714

0714-0-33-XX-07-XX-10-0


Wire crimp termination. Accepts wire sizes 16 AWG Max. / 20 AWG Min.



0778

0778-0-18-XX-07-XX-10-0


Press-fit in .143 mounting hole. Accepts wire sizes up to 14 AWG



9177

9177-0-18-XX-07-XX-10-0


Press-fit in .151 mounting hole. Accepts wire sizes up to 16 AWG



5391

5391-0-15-XX-07-XX-10-0


Solder mount in .159 min. mounting hole. Also available on 16mm wide carrier tape: 1,825 parts per 13" reel. See page 194.19 for Tape & Reel details



8837

8837-0-15-XX-14-XX-10-0


Solder mount in .159 min. mounting hole



9837

9837-0-15-XX-14-XX-10-0


Solder mount in .159 min. mounting hole



8994

8994-0-15-XX-07-XX-04-0

Press-fit in .128 mounting hole



SPECIFICATIONS:

Shell Material: Brass Alloy 360, 1/2 Hard

Contact Material: Beryllium Copper Alloy 172, HT

Dimensions: Inches

Tolerances On: Lengths: ±.005

Diameters: ±.002

Angles: ± 2°



ORDER CODE: XXXX - X - XX - XX - XX - 10 - 0

BASIC PART #

SPECIFY SHELL FINISH:

01 200 μ" TIN/LEAD OVER NICKEL

◆ 80 200 μ" TIN OVER NICKEL (RoHS)

◆ 15 10 μ" GOLD OVER NICKEL (RoHS)

SPECIFY CONTACT FINISH:

01 200 μ" TIN/LEAD OVER NICKEL

◆ 80 200 μ" TIN OVER NICKEL (RoHS)

◆ 27 30 μ" GOLD OVER NICKEL (RoHS)

SELECT CONTACT:

#07 or #14 CONTACT (DATA ON PAGE 261)

(For alternate contact choices, see group H on page 248)



Mill-Max Mfg. Corp. • 190 Pine Hollow Road, P.O. Box 300, Oyster Bay, NY 11771 • 516-922-6000 • Fax: 516-922-9253 • www.mill-max.com