



© COPYRIGHT 2014 BY INDUSTRIAL FIBER OPTICS, INC.
ALL RIGHTS RESERVED.

LIGHT PIPE PREPARATION / INSTALLATION:



NOTES:


1. ROHS COMPLIANT
2. UL 94V-2 FLAMMABILITY RATING
3. -40°C TO 85°C OPERATING TEMPERATURE
4. SUITABLE FOR LIGHT PIPE WITH $\varnothing 2.2\text{mm}$ JACKET AND OPTICAL CORE NO GREATER THAN $\varnothing 1.5\text{mm}$
5. DO NOT INSTALL PRIOR TO SOLDERING
6. FOR BEST RESULTS USE ONLY NARROW VIEWING ANGLE NON-DIFFUSED LEDS WITH OUTPUT POWER GREATER THAN 100mcd
7. NOT RECOMMENDED FOR DATA COMMUNICATIONS



METRIC

REVISIONS

REV	DESCRIPTION	ECO	DATE	DWN	APVD
A	Initial release		11/12/2008	BB	RD
B	Revised strip length from $1.0 \pm .25$	0034	9/17/2009	BB	KS
B1	Redrew, added overall dimensions		7/21/2014	BB	WR



PART IS MADE OF BLACK NYLON

UNLESS OTHERWISE SPECIFIED

DIMENSIONS MILLIMETERS [IN.]

DIMENSIONS ARE FOR
REFERENCE ONLY
NO TOLERANCES MAY BE
IMPLIED FROM THIS DOCUMENT

PRODUCT 51 0410

MATERIAL Nylon 66

FINISH None

DRAWN BY B. Bidwell

DATE 7/22/2014

CHECKED BY W. Rowe

DATE 7/22/2014

Industrial Fiber Optics
TEMPE, AZ 85281

NAME

SMT LED to Light Pipe

SIZE A

SCALE 2:1

PART NUMBER
51 0310

REV
B1

DO NOT SCALE DRAWING

Sheet 1 of 1