PowerCool Series DA-014-12-02
MFG Part Number: DA-014-12-02-00-00

PowerCool Series Thermoelectric Cooler Assembly

The DA-014-12-02 is a Direct-to-Air Thermoelectric Cooler Assembly that uses impingement flow to transfer heat. It offers dependable, compact performance by cooling objects via conduction. Heat is absorbed through a cold plate and dissipated thru a high density heat exchanger equipped with an air ducted shroud and brand name fan. It has a maximum Qc of 12 Watts when ΔT = 0 and a maximum ΔT of 50 °C at Qc = 0.


Features

- Compact design
- Precise temperature control
- Reliable solid-state operation
- Low noise
- RoHS-compliant


Applications


- Medical Diagnostic and Analytical Instrumentation
- Thermoelectric Coolers and Assemblies for Medical Applications
- Liquid Cooling Options for PET and SPECT Scanners
- Cooling for Centrifuges
- High-Performance Liquid Chromatography (HPLC)
- Heating and Cooling for Liquid Chromatography Systems






ELECTRICAL AND THERMAL PERFORMANCE







Coefficient of Performance (COP = Qc/Pin)
Tambient = 35°C | Tcontrol = 20°C




Coefficient of Performance (COP = Qc/Pin)
Tambient = 35°C | Tcontrol = 20°C




Total Heat Dissipated at Hot Side (Qh=Qc+Pin)
Tambient = 35°C | Tcontrol = 20°C




Total Heat Dissipated at Hot Side (Qh=Qc+Pin)
Tambient = 35°C | Tcontrol = 20°C



Heat Pumped at Cold Side (Qc)
Voperating = 12.02 Volts | Ioperating = 1.43 Amps




Coefficient of Performance (COP = Qc/Pin)
Voperating = 12.02 Volts | Ioperating = 1.43 Amps




SPECIFICATIONS

Heat Transfer Mechanism, Cold Side	Direct - Conduction
Heat Transfer Mechanism, Hot Side	Air - Forced Convection
Operating Temperature Range	-10°C to 44°C
Supply Voltage	12.0 VDC nominal / 15.0 VDC maximum
Current Draw	1.8 A running / 2.3 A startup
Power Supply	22.0 Watts
Performance Tolerance	10%
Hi-Pot Testing	No Testing
Fan MTBF	50,000 hours
Weight	0.20 kg
Panel Mounting	Flush Mount

MOUNTING HOLE LOCATION



WIRING SCHEMATIC



NOTES

[1]For indoor use only

[2]Units are generally maintenance free, however occasionally it is recommended to clean the heat sinks and fans of debris. This is best done with compressed air.

Any information furnished by Laird and its agents, whether in specifications, data sheets, product catalogues or otherwise, is believed to be (but is not warranted as being) accurate and reliable, is provided for information only and does not form part of any contract with Laird. All specifications are subject to change without notice. Laird assumes no responsibility and disclaims all liability for losses or damages resulting from use of or reliance on this information. All Laird products are sold subject to the Laird Terms and Conditions of sale (including Laird's limited warranty) in effect from time to time, a copy of which will be furnished upon request.

© Copyright 2019-2022 Laird Thermal Systems, Inc. All rights reserved. Laird™, the Laird Ring Logo, and Laird Thermal Systems™ are trademarks or registered trademarks of Laird Limited or its subsidiaries.

Revision: 00 Date: 06-01-2022

Print Date: 06-15-2022