# CHIPQUIK® CQ4300LF-0.5

Datasheet revision 1.1 www.chipquik.com

## Liquid Flux Alcohol-Based No-Clean Water-Washable in 15ml (0.5oz) Squeeze Bottle




### Product Highlights

No-Clean and Water-Washable
Low solids
Alcohol-Based
Ideal for all rework, solder, and de-solder applications
Excellent wetting
Easily cleaned with isopropyl alcohol (IPA) or hot water (60°C+)
Can be used with Leaded and Lead-Free applications
**RoHS 3 and REACH compliant**

### Specifications

| | |
|---|---|
| Flux Type: | No-Clean Water-Washable Liquid (for Leaded and Lead-Free applications) |
| Flux Classification: | ORL0 |
| Specific Gravity: | 0.8 |
| Packaging: | 15ml Squeeze Bottle |
| Shelf Life: | Refrigerated >24 months, Unrefrigerated >24 months |

### Storage and Handling

Store refrigerated or at room temperature 3-25°C (37-77°F). The liquid flux can be allowed to freeze. Freezing will not degrade this product. Allow 4 hours for flux to reach an operating temperature of 20-25°C (68-77°F) before use.

### Transportation

This product requires ground shipping. Shipping below 0°C (32°F) or above 25°C (77°F) for normal transit times by ground will not impact this product's stated shelf life.

### Cleaning

This is a no-clean and water-washable liquid flux, post-use cleaning is not required. However, if post-use cleaning is desired, the non-corrosive non-conductive residue can be cleaned off using hot water (60°C+) or isopropyl alcohol (IPA).

### Conforms to the following Industry Standards:

| | |
|---|---|
| J-STD-004B, Amendment 1 (Solder Fluxes): | Yes |
| RoHS 3 Directive 2015/863/EU: | Yes |


© 1994-2022 Chip Quik® Inc.