


| JKL LAMP PART NUMBER | COLOR 6900°KELVIN | STARTING CIRCUIT VOLTAGE VS (Vrms) | OPERATING LAMP VOLTAGE VL (Vrms) | OPERATING LAMP CURRENT IL (mArms) | BRIGHTNESS (Cd/m2) | *RATED LIFE (HRS) |
|---|---|---|---|---|---|---|
| CF20277-28B | x = .325<br>y = .295 | 1560 @ 0°C | 625 @ 5mA | 5.0 TYP. | 38,000 TYP. | 20,000 MIN.<br>40,000 AVG. |

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OFTHE INITIAL RATING.

| REV. NO. | DESCRIPTION/ECO NUMBER | APPV'D DATE |
|---|---|---|
| | RELEASED & CANCEL P-0404-13 | 4/22/04 |

METRIC
THIRD ANGLE PROJECTION

DIMENSIONS ARE IN MILLIMETERS
TOLERANCE UNLESS OTHERWISE SPECIFIED
1 PL +/- 0.2
2 PL +/- 0
ANGLE +/- 0

DRAWN BY: L. WENGSTROM
APPV'D BY / DATE: J.K. 4/22/04

- CAD DRAWING -
MANUAL REVISIONS NOT PERMITTED

JKL COMPONENTS CORPORATION

TITLE: MINIATURE COLD CATHODE FLUORESCENT LAMP

SIZE: A
FSCM NO.: 55335
DRAWING NO.: CF20277-28B
SCALE: NONE
RELEASED DATE: 4/22/04
REVISION DATE:
REV. NO.:
SHEET: 1 OF 1